

# CREATEX GmbH

## Product Safety Data Sheet

### 1: Product and Company Identification

Product name: Createx Airbrush Colour transparent, opaque, fluorescent, pearlescent, iridescent

Use: Airbrush Colours for all surfaces (assorted colours)

Company: Createx Handels-GmbH, Kirchhoffstr. 7, D 24568 Kaltenkirchen  
Phone: +49-4191-882 77 – Fax: +49-4191-859 12 e-mail: [info@createx.de](mailto:info@createx.de)

### 2: Composition/information on ingredients

Acrylic polymer	~ 20 - 25 %
Water	~ 58 %
Aqueous pigment dispersion	~ 8 – 12 %
Glycols	~ 2 %
Water softener and other proprietary ingredients	~ 3 %

### 3: Hazards identification

unlikely to cause immediate irritation. No substances are present in concentrations regarded to present health hazards (Art. 3 of Directive 88/379)

### 4: First aid measures

Eyes	flush with water for 10 mins. And consult physician if irritation persists
Skin	wash the skin thoroughly with water before eating, drinking or smoking
Inhalation	remove the person affected to fresh air. Consult a Doctor in case of adverse effects
Ingestion	Do not indulge vomiting. If victim is conscious give water. No measures are needed but if adverse health effects follow, consult a Doctor

### 5: Fire fighting measures

product is not combustible (standard fire fighting measures appropriate to the environment)

### 6: Accidental release measures

Personal precautions	: no special measures are needed
Environmental precautions	: do not allow the product to enter public drainage system or open water
Methods for cleaning up	: absorb with sand or sawdust, dispose of when dry

### 7: Handling and storage

Handling	: Ideal storage temperature between 1° C and 35° C. Paint does not withstand freezing. Keep bottle closed when not in use.
----------	--

## 8: Exposure controls

no special precautions are needed beyond clean working conditions and safe handling practises.  
Always use with adequate ventilation.

## 9: Physical and chemical properties

form	liquid
flash point	not applicable
Density	ca. 1.1 gr/cc
Viscosity	150mPa.s (Brookfield R1, 60rpm, 20°C)
volatile content	less than 0.5 %
pH	8.7
solubility in water	totally soluble
drying time	20-30 minutes
boiling point	93 – 102° C

## 10: Stability and Reactivity

stable at normal conditions

## 11: Toxicological information

TLV: none established. According to the European Legislation 67/548/CEE of 20.4.1994 Liquid Acrylic is not toxic, not noxious and not irritative

## 12: Ecological information

Do not allow to enter soil, waterways or waste water

## 13: Advice on disposal

Disposal in accordance with federal, state and local regulations (suitable incineration plants). In some countries, incineration is not permitted

## 14: Transportation information

Liquid acrylic is not a hazardous product

## 15: Reglimentary information

Classified not hazardous. This product does not require labelling.

Symbol CE: none

## 16: Other information

This information is a safety guide only for handling and storing this product, it is not a specification of quality.